

A1  
concluded

body formed on and surrounding said base plate including  
on a side and bottom surface of the base plate;

said base plate projecting out of said housing body  
on at least one side, thus forming a cantilevered  
attachment section.

A2

5. (Amended) The housing according to claim 1, wherein  
at least one soldering pin is stamped out from said base  
plate, said soldering pin being perpendicularly bent upwards  
inside said housing body.

6. (Amended) The housing according to claim 3, wherein  
at least on soldering pin is stamped out from said contact  
plate, said soldering pin being perpendicularly bent upwards  
inside said housing body.

A3

8. (Amended) The housing according to claim 1, wherein  
said housing body has an open side opposite said base plate  
and a removable cover, said cover fitting on the open side of  
said housing body and being connected to said housing body by  
an interaction of lock-in openings and corresponding support  
projections.

Add the following claim:

A4

12. An electronic monitoring device on a vehicle part  
such as a lead accumulator, said device comprising:  
a housing with a metallic load-bearing base plate

Serial No. 09/998,105

and an injection molded, generally parallelepipedal housing body formed on and surrounding said base plate including on a side and bottom surface of the base plate,

a printed circuit board, and

at least one soldering pin being stamped out from said base plate,

said soldering pin being perpendicularly bent upwards inside said housing body, said soldering pin penetrating into a corresponding opening of said printed circuit board to contact said printed circuit board.

A4  
encl 24

25  
B1